

AXIAL ROTARY FLAIL MOWER FOR "HILLSIDE TRACTORS"

Grass-scrub machine suitable for all terrains

# Bravia

Special linkage for tool carriers  
and hillside tractors  
Reduced linkage overhang for maximum  
transport lift. Compact design copes easily  
with crossing drainage channels

Angle-gearbox is equipped  
with mechanical reverser to allow mowing  
in one direction and scrub cutting in the other

## System Sensiv'

Polyurethane bushes fitted  
between frame and chassis allow  
working flexibility and limit  
vibration-transmission to the tractor

Bossed positively located  
linkage pins provide maximum  
protection against wear

Anti-projectile  
side flaps

Cutting height  
adjustable in 3 positions

Flush rotor bearing housing  
for mowing closer to obstacles...  
fences, signposts etc

"Ski profile"  
forged skid shoes

Easily raised 10-section reinforced front  
interchangeable flap for scrub cutting

Rotor bearing greasing  
can be carried out with belt  
guard removal

Rotor diameter 150mm (6")

Equipped as standard with 108 'Y' profile blades  
and 54 14 mm-bolted shackles.



## Bravia

### Specifications

Width of cut	1.96 m
Overall width	2.19 m
Weight	500 kg
Rotor diam	150 mm
Feeler roller diameter	133 mm
No of blades	108 "Y" type
Direction of drive	reversible
Belt	Poly "V" type
Height of cut (3 positions)	5/8.5/12 cm (2/3.5/4 ¾")
PTO	540 rpm



166, rue Ampère  
54714 LUDRES Cedex / FRANCE

Tél. : +33 (0)3 83 25 69 60

Fax : +33 (0)3 83 26 12 85

e-mail : [contact@norem.fr](mailto:contact@norem.fr)

[www.norem.fr](http://www.norem.fr)